

LEXMARK E360DN



Print Speed (A4, Black): Up to	38 ppm
Print Speed (A4, Black) Duplex: Up to	18 spm
Print Speed (Letter, Black): Up to	40 ppm
Print Speed (Letter, Black) Duplex: Up to	18 spm
Time to First Page (Black) As fast as	6.5 seconds
Print Resolution, Black	1200 Image Quality 1200 x 1200 dpi 2400 Image Quality 600 x 600 dpi
Processor	400 MHz
Memory, Standard	32 MB
Memory, Maximum	288 MB
Expandable Memory Options	Yes
Apple Macintosh Operating Systems Supported	Apple Mac OS X (10.2 or later) Apple Mac OS 9.2
Citrix MetaFrame	Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0 Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5 Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64
Linux Operating Systems Supported	Linpus Linux Desktop 9.2, 9.3 Red Hat Enterprise Linux WS 3.0, 4.0, 5.0 SUSE Linux Enterprise Server 8.0, 9.0, 10, 11 SUSE Linux Enterprise Desktop 10 openSUSE 10.2, 10.3, 11.0, 11.1 Linspire Linux 6.0 Debian GNU/Linux 4.0 Red Flag Linux Desktop 5.0, 6.0 Ubuntu 7.10 Ubuntu 8.04 LTS SUSE Linux Enterprise Desktop 11 Debian GNU/Linux 5.0 Ubuntu 8.10, 9.04
Microsoft Windows Operating Systems Supported	Microsoft Windows 2000 Microsoft Windows XP Microsoft Windows Server 2003 Microsoft Windows XP x64 Microsoft Windows Server 2003 running Terminal Services Microsoft Windows 2000 Server running Terminal Services Microsoft Windows Server 2003 x64 Microsoft Windows Server 2003 x64 running Terminal Services Microsoft Windows Vista

	<p>Microsoft Windows Vista x64 Microsoft Windows Server 2008 Microsoft Windows Server 2008 x64 Microsoft Windows Server 2008 running Terminal Services Microsoft Windows Server 2008 x64 running Terminal Services Microsoft Windows 7</p>
Novell Operating Systems Supported	<p>Novell® Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS) Novell NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)</p>
UNIX Operating Systems Supported	<p>Sun Solaris SPARC 8, 9, 10 Sun Solaris x86 10 HP-UX 11.11, 11.23, 11.31 IBM AIX 5.2, 5.3, 6.1</p>
Other Operating Systems Supported	<p>IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform Virtually any platform supporting TCP/IP</p>
Paper Handling Standard	<p>150-Sheet Output Bin Integrated Duplex Single Sheet Exit 250-Sheet Input Tray 50-Sheet Multipurpose Feeder</p>
Paper Handling Optional	<p>550-Sheet Drawer Only one drawer may be installed at a time 250-Sheet Drawer</p>
Paper Input Capacity, Standard: Up to	300 pages 75 gsm bond
Paper Input Capacity, Maximum: Up to	850 pages 75 gsm bond
Paper Output Capacity, Standard: Up to	150 pages 75 gsm bond
Paper Output Capacity, Maximum: Up to	150 pages 75 gsm bond
Envelope Capacity	7
Finishing Option?	No
Number of Paper Inputs, Standard	2
Number of Paper Inputs, Maximum	3
Media Types Supported	<p>Card Stock Envelopes Paper Labels Plain Paper Transparencies Refer to the Card Stock & Label Guide</p>
Media Sizes Supported	<p>10 Envelope 7 3/4 Envelope 9 Envelope A4 A5 B5 Envelope C5 Envelope DL Envelope A6 Card Executive Folio JIS-B5 Legal Letter Statement Universal Oficio</p>
Supplies Yield	<p>*Average standard page yield value declared in accordance with ISO/IEC 19752. 9,000*-page High Yield Toner Cartridge 3,500*-page Toner Cartridge</p>

Standard Ports	Centronics IEEE 1284 Bidirectional Parallel Ethernet 10/100BaseTX (RJ-45) USB 2.0 Specification Hi-Speed Certified (Type B)
Optional Network Ports	Lexmark N4050e 802.11g Wireless Print Server (Print Only) External MarkNet™ N7020e Gigabit Ethernet
Network Management Protocols	HTTP WINS IGMP APIPA (AutoIP) DHCP ICMP DNS SNMPv2c Bonjour DDNS mDNS ARP NTP Telnet Finger
Network Protocol Support	TCP/IP IPv4 AppleTalk™ TCP/IP IPv6 TCP UDP
Network Printing Methods	LPR/LPD Direct IP (Port 9100) HTTP Enhanced IP (Port 9400) FTP, TFTP IPP 1.1 (Internet Printing Protocol)
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide 2 PCL bitmap fonts 39 scalable PPDS fonts 5 PPDS bitmap fonts 84 scalable PCL fonts 89 scalable PostScript fonts OCR-A, OCR-B scalable PCL 5e fonts For more information, refer to the Technical Reference.
Printer Languages (Standard)	PCL 5e Emulation PCL 6 Emulation Personal Printer Data Stream (PPDS) PostScript 3 Emulation
Packaged Size (mm - H x W x D)	355 x 460 x 420 mm
Size (mm - H x W x D)	260 x 406 x 370 mm
Weight (kg)	13.83 kg
Noise Level, Idle	inaudible dBA
Print Noise Level, Operating	53 dBA
Product Warranty	1-Year Exchange, Return-To-Base
Product Certifications	Blue Angel (RAL-UZ-122), FCC Class B, UL 60950-1 3rd Edition, U.S. FDA, IEC 320-1, CSA, ICES Class B, Energy Star, CE Class B, CB IEC 60950-1, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, N Mark, ACA C-tick Class B, CCC Class B, BSMI Class B, MIC, EK Mark, PSB
Duty Cycle Notes	"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

	"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.
Specified Operating Environment	Temperature: 16 to 32°C Altitude: 0 - 2500 Metres Humidity: 8 to 80% Relative Humidity for Temperatures less than 25.5°C